

# Westdale - Single Handle Tub & Shower Faucet



- \* Pressure Balanced Premium Ceramic Cartridge (Type F)
- \* Solid Brass Waterway Construction with 1/2" -14 NPT Connection
- \* Back to Back Installation Option
- \* Integral Stops, Diverter Tub Spout
- \* 4-3/4" 10 Function Showerhead
- \* Stainless Steel Shower Arm
- \* Stainless Steel Plate
- \* Zinc Die Cast Tub Spout
- \* Showerhead Flow Rate: 1.5 GPM (5.7 L/MIN) MAX @ 80PSI - Meets EPA WaterSense®
- \* Tub Spout Flow Rate: 6.5 GPM (24.7 L/MIN) MAX @ 80PSI
- \* 100% Pressure System Tested
- \* Lifetime Limited Warranty; 5 year Warranty from Date of Purchase for Commercial Use

Project / Job Name	
Architect / Engineer	
Contractor	
Model	
Quantity	



## Model No. :

192-8099 (CH)


192-8100 (BN)

192-8101 (MB)  
 (Shown Model)

192-8102 (BS)



## Showerhead Functions :



### Product Compliance:

- ASME A112.18.1 / CSA B125.1
- ANSI A117.1 (ADA)
- ASSE 1016